

Model : T1005 & T1006

UHF handheld transmitter,
T1005(Dynamic) – T1006(Condenser)

The Turbo Professional Series represents a massive leap forward in both specification and design.

The T1005 and T1006 handheld transmitters are designed to operate with the T1001 and T1002 UHF receivers

Product Features

- Option of Dynamic capsule (T1005) or Condenser capsule (T1006)
- Low power consumption using 2 x AA batteries
- Programmable LCD display
- Battery level indicator
- Charging input port for rechargeable battery operation
- Up/Down channel control
- Choice of coloured microphone id caps supplied

Optional accessories

- G130BB – Microphone holder
- G122CA – Microphone windshield

Specifications

Carrier Frequency Range.....UHF band 842 ~ 865 MHz
 RF Power Output.....10mW (max.)
 Oscillator.....PLL synthesized
 Frequency Stability.....±0.005%
 Maximum Deviation.....±48KHz
 Spurious Emission.....>60dB Below Carrier frequency
 T.H.D.< 1% (at 1KHz)
 Tone Signal.....32.768 KHz
 Dynamic capsule (T1005) response.....50 Hz to 16kHz
 Condenser capsule (T1006) response.60 Hz to 17kHz
 Operating Voltage.....3v DC , 2 x AA Dry Cell or NiMh
 Current Consumption.....70mA ± 5mA
 Dimension (mm).....(Length and dia) 265mm 62mm



T1005/6 handheld microphone



T1005/6 with the battery cover removed